

CONTRACTOR RANGE

PSKS ENCLOSURES

**PEEKN
SERVICES**

**Industrial Electrical
& IT Solutions**

Heathcote, NSW, 2233
Business Reg: BN98476366
ABN:15 924 167 896

sales@peeknservices.com.au

Tel: 0448 085 061

06:30 ~ 20:30 7 Days



**Cost effective enclosure solutions for
domestic, commercial & industrial
applications**

PSKS ENCLOSURE SPECIFICATIONS

Features:

- Heat moulded plastic enclosure.
- Self extinguishing materials as per ASTM D635.
- 70% Polyester + 30% Fibreglass providing a high degree of mechanical protection and perfect for use in highly corrosive environments.
- Weatherproof, integrated rain canopy over door.
- Enclosure can be reversed to accommodate LHS or RHS hinged door.
- Door opening > 180°, Stainless steel hinges
- Zinc plated mounting plate included.
- Wall mounting brackets available as accessories.

Degree of protection:

- Complies with IEC60529, EN60529/10.91 & GB4208-93 standards.
- Rated to IP66
- Temperature range -30°C ~ +120°C

Material:

- Polyester / Fibre glass.
- Thickness – Mounting plate, 2.5mm

Surface finish:

- Light grey RAL 9002

CONTRACTOR RANGE

PEEKN
SERVICES

Heathcote, NSW 2233

TEL: 0448 085 061

ABN 15 924 167 896

FAX: 02 9548 6818

sales@peeknservices.com.au

www.peaknservices.com.au

PSKS ENCLOSURE SIZES

PART #	Width	Height	Depth
PSKS253014	250	300	140
PSKS304020	300	400	200
PSKS404020	400	400	200
PSKS405020	400	500	200
PSKS406023	400	600	230
PSKS506023	500	600	230
PSKS608030	600	800	300



PSKS ACCESSORIES

Key lock inserts

Wall mounting brackets

NOT ENOUGH?

**ASK ABOUT OUR
ENCLOSURE PLUS
RANGE**

215 x 315 x 170

~

835 x 1035 x 300

0448 085 061

sales@peeknservices.com.au

IP66

ELKS	WIDTH	HEIGHT	DEPTH
PC01	215	315	170
PC02	315	415	170
PC03	415	515	230
PC04	415	615	230
PC05	535	735	270
PC06	635	835	300
PC07	835	1035	300

AVAILABLE ACCESSORIES

Mounting Plates – Pertinax
Mounting Plates – ZP Steel
Full Cover Plates (escutcheons)
Hinges for cover plates

Air Vents (IP44)
Wall Mounting Brackets
T Handles
Keyed Lock Inserts

EPR COMPONENTS

Take advantage of the complementary EPR Component range on offer with any purchase of “Enclosure Plus Range” products.

These components are available for use with our “Contractor Range” however a M.O.V. may apply.

CLIMATE CONTROL:	<ul style="list-style-type: none"> - Heaters - Fan & Filter systems - Hygro / Thermo stats etc
CONTACTORS:	<ul style="list-style-type: none"> - 2, 3 or 4 Pole, AC & or DC Control - 9A ~ 1250A depending on Contactor - DIN Rail or Panel mounted versions available - Overloads, Auxiliaries, DOL Starters etc.
PILOT DEVICES:	<ul style="list-style-type: none"> - Push buttons, Selector Switches, Pilot lights - Enclosed push buttons, Emergency stop stations - Cam switches, 25 ~ 80A
POWER DISTRIBUTION:	<ul style="list-style-type: none"> - 2 / 3 / 4 Pole Isolators, Main Switches, MCB's, RCD's, RCCD's & RCBO's etc. - DIN rail mounted or IP Rated enclosure solutions...
PV SOLUTIONS:	<ul style="list-style-type: none"> - Dedicated DC breakers, Isolators & contactors
RELAYS:	<ul style="list-style-type: none"> - 1 / 2 / 3 or 4 Pole, Mechanical or Solid state. - 6A ~ 90A (depending on load type).
TERMINAL BLOCKS:	<ul style="list-style-type: none"> - 2.5 ~ 95mm (232A), DIN rail mounted, melamine, CT etc. - Feed through, multilevel, PCB mounted etc. - Earth & Neutral links
TIMERS:	<ul style="list-style-type: none"> - Analogue, Digital & Pneumatic
WIRING ACCESSORIES:	<ul style="list-style-type: none"> - Ducting, (Slotted or plain), wire wrap etc. - Cable glands, Hole plugs / Bushes, cable ties & clips etc. - DIN Rail & accessories, Insulators etc.

CONTRACTOR RANGE

**PEEKN
SERVICES**



**PSPK RANGE
POLYCARBONATE
80 MODELS**



**PSKLM RANGE
MILD STEEL
19 MODELS**



**PSCE RANGE
MILD STEEL
27 MODELS**



**PSKLS RANGE
STAINLESS STEEL
18 MODELS**



**PSKS RANGE
POLYESTER
7 MODELS**



**PSTB RANGE
MILD STEEL
16 MODELS**

**PSSS RANGE
STAINLESS STEEL
19 MODELS**



**PEEKN
SERVICES**

Heathcote, NSW 2233

TEL: 0448 085 061

ABN 15 924 167 896

FAX: 02 9548 6818

sales@peeknservices.com.au

www.peaknservices.com.au